



TECHNICAL SHEET



FA 20 500 12

Designation: Retractable Fall Arrester Olympe in webbing


- Width of the webbing: 25 mm.
- Nearly indestructible casing made up of high impact strength Polymer to prevent breakage.
- Lateral handle for carrying the block.
- Minimum breaking strength: > 15 Kn.

Connectors:

1 steel screw-locking karabiner, opening 17 mm, ref. FA 50 101 17 and 1 steel snap hook with swivel and fall indicator, opening 21 mm.

Compliance: Conforms to EN 360:2002.

- Certified for a horizontal use when is used with the lanyard ref. FA 40 304 15 connected to the webbing of the block.



Length: 12 mtrs.

Material of the components :

Casing : Polyethylene anti shock
 Webbing : Polyester
 Connectors : Steel

HS code	Carton Size / Pieces	Unit Weight
84289090	60x40x24 / 04	6.10 Kg

AET : N° 4023 Issue 4 Extension 2

Satra Technology Centre, N°0321
 Wyndham Way, Telford Way, Kettering,
 Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
 Unit 202B, Worle Parkway,
 Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 02/15

ZI les portes du Dauphiné
 4 rue de l'Aigue
 69 780 St Pierre de Chandieu – France
 Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
 www.kratossafety.com info@kratossafety.com

